

SECTION 1. IDENTIFICATION

Product Name:	BBO-BASE AO
Synonyms:	Atmospheric Gas Oil
Product Use:	Drilling, Completion & Production Fluid Base Oil.
Restrictions On Use:	Not Available
Manufacturer/Supplier:	Barron Base Oil Corporation
	Suite #323, 400-5 th Ave. S.W.
	Calgary, Alberta
	T2P 0L6
Phone Number:	403-618-5213
Emergency Phone Number:	Canutec 613-996-666 or *666
Date of Preparation of SDS:	November 20, 2018

SECTION 2. HAZARD IDENTIFICATION

GHS INFORMATION

Classification: Skin Irritation, Category 2

Eye Irritation, Category 2B Carcinogenicity, Category 1B

LABEL ELEMENTS

Hazard Pictogram(s):



- Signal Word: Danger
- Hazard Causes skin irritation.
- Statements: Causes eye irritation.

May cause cancer.



Precautionary Statements

Prevention: Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Wash thoroughly after handling.

Wear protective gloves, protective clothing and eye protection.

Response: IF ON SKIN: Wash with plenty of water.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

If exposed or concerned: Get medical advice/attention.

If skin irritation occurs: Get medical advice/attention.

If eye irritation persists: Get medical advice/attention.

Take off contaminated clothing and wash it before reuse.

Storage: Store locked up.

Disposal: Dispose of contents/container in accordance with applicable regional,

national and local laws and regulations.

Hazards Not Otherwise Classified: Not applicable.

Ingredients with Unknown Toxicity: 100% of this product mixture consists of ingredient(s) of

unknown acute toxicity.

This material is considered hazardous by the OSHA Hazard Communication Standard, (29 CFR 1910.1200).

This material is considered hazardous by the Hazardous Products Regulations.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous Ingredient(s)	Common name / Synonyms	CAS No.	% wt./wt.
Gas oils (petroleum), straight-run, high- boiling	Not available.	68915-97-9	100
Polycyclic Aromatic Hydrocarbons Benzene, dimethyl-	Not available. Xylene	130498-29-2 1330-20-7	variable <0.01

Product Identifier: Date of Preparation: Date of Last Revision:



SECTION 4. FIRST AID MEASURES

Inhalation:	If inhaled: Call a poison center or doctor if you feel unwell.
	Acute and delayed symptoms and effects: May cause respiratory irritation. Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain. This product may contain small amounts of Hydrogen sulphide which may accumulate in confined spaces. Inhalation of Hydrogen sulphide may cause loss of sense of smell, major irritation of the respiratory tract, headache, nausea, vomiting, dizziness, and fluid buildup in the lungs (pulmonary edema), which can be fatal. At 300 ppm unconsciousness may occur after 20 minutes. From 300 to 500 ppm, death can occur within 1 to 4 hours of continuous exposure. At 500 ppm the respiratory system is paralyzed, the victim collapses almost instantaneously, and death can occur after exposure of only 30 to 60 minutes. Above 500 ppm Hydrogen sulphide may cause immediate loss of consciousness; death is rapid, and possibly immediate.
Eye Contact:	If in eyes: Rinse cautiously with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
	Acute and delayed symptoms and effects: Causes eye irritation. Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.
Skin Contact:	If on skin: Wash with plenty of water. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse.
	Acute and delayed symptoms and effects: Causes skin irritation. Signs/symptoms may include localized redness, swelling, and itching.
Ingestion:	If swallowed: Immediately call a poison center or doctor. If vomiting occurs
	naturally, have victim lean forward to reduce the risk of aspiration. Do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person.
	Acute and delayed symptoms and effects: May be fatal if swallowed and enters airways. May cause gastrointestinal irritation. Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.



General Advice:	In case of accident or if you feel unwell, seek medical advice immediately (show the label or SDS where possible). If exposed or concerned: Get medical advice/attention.
Note to Physicians:	Symptoms may not appear immediately. For inhalation of Hydrogen Sulphide, consider oxygen.

SECTION 5. FIRE FIGHTING MEASURES

FLAMMABILITY AND EXPLOSION INFORMATION

When heated, this material may evolve toxic and flammable Hydrogen sulphide.

Sensitivity to Mechanical Impact: This material is not sensitive to mechanical impact.

Sensitivity to Static Discharge:	This material is sensitive to static discharge at temperatures at or above flash point.	
MEANS OF EXTINCTION		
Suitable Extinguishing Media:	Small Fire: Dry chemical, CO2, water spray or regular foam.	
	Large Fire: Water spray, fog or regular foam. Move containers from fire area if you can do it without risk.	
Unsuitable Extinguishing Media: Not available.		
Products of Combustion:	Oxides of carbon. Oxides of sulphur. Oxides of nitrogen. Aldehydes.	
Protection of Firefighters:	Fire may produce irritating, corrosive and/or toxic gases. Runoff from fire control or dilution water may cause pollution. Hydrogen sulphide is heavier than air and may collect in low lying areas and confined spaces. Wear positive pressure self-contained breathing apparatus (SCBA). Structural firefighters' protective clothing will only provide limited protection.	

SECTION 6. ACCIDENTAL RELEASE MEASURES

Emergency Procedures: Keep unauthorized personnel away. Stay upwind. Keep out of low areas. Ventilate closed spaces before entering. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area).

Product Identifier: Date of Preparation: Date of Last Revision:



BBO-BASE AO Personal Precautions: Do not touch or walk through spilled material. Use personal protection recommended in Section 8. Don full-face, positive pressure, self-contained breathing apparatus. Environmental Precautions: Keep out of drains, sewers, ditches, and waterways. Methods for Containment: Stop leak if without risk. Do not flush to sewer or allow to enter waterways. Methods for Clean-Up: Absorb or cover with dry earth, sand or other noncombustible material and transfer to containers. Other Information: See Section 13 for disposal considerations

SECTION 7. HANDLING AND STORAGE

Handling:

Do not swallow. Do not breathe mist, vapours, or spray. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wash thoroughly after handling. See Section 8 for information on Personal Protective Equipment.

Storage:

Store locked up. Store away from incompatible materials. See Section 10 for information on Incompatible Materials. Keep out of the reach of children. Tank vapour spaces should be regarded as hazardous. Structural materials and lighting and ventilation systems should be corrosion resistant.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Guidelines Component

Gas oils (petroleum), straight-run, high-boiling [CAS No. 68915-97-9]

ACGIH: A2; Exposure by all routes should be carefully controlled to levels as low as possible (2009); For Mineral oil, excluding metal working fluids; Poorly and mildly refined

OSHA: 5 mg/m³ (TWA); For Oil mist, mineral. Product Identifier: BBO-BASE AO Date of Preparation: November 20, 2018 Date of Last Revision: March 5, 2020



Polycyclic Aromatic Hydrocarbons [CAS No. 130498-29-2]

ACGIH: A2; BEI; Exposure by all routes should be carefully controlled to levels as low as possible (1990); For Benz[a]anthracene

OSHA: 0.2 mg/m³ (TWA); For benzene-soluble fraction.

Xylene [CAS No. 1330-20-7]

ACGIH: 100 ppm (TWA); 150 ppm (STEL); A4; BEI (1992)

OSHA: 100 ppm (TWA), 435 mg/m³ (TWA);

150 ppm (STEL) [Vacated];

TWA: Time-Weighted Average **STEL:** Short-Term Exposure Limit **C:** Ceiling

Engineering Controls:

Use ventilation adequate to keep exposures (airborne levels of dust, fume, vapour, gas, etc.) below recommended exposure limits.

PERSONAL PROTECTIVE EQUIPMENT (PPE)



Eye/Face Protection:	Wear safety glasses. Ensure that eyewash stations are close to the workstation location. Use equipment for eye protection that meets the standards referenced by CSA Standard CAN/CSA-Z94.3-92 and OSHA regulations in 29 CFR 1910.133 for Personal Protective Equipment.
Hand Protection:	Wear protective gloves. Consult manufacturer specifications for further information.
Skin and Body Protection:	Wear protective clothing.
Respiratory Protection:	If engineering controls and ventilation are not sufficient to control exposure to below the allowable limits then an appropriate NIOSH/MSHA approved air-purifying respirator that meets the requirements of CSA Standard CAN/CSA-Z94.4-11, or self-contained breathing apparatus must be used. Supplied air breathing apparatus must be used when oxygen concentrations are low or if airborne concentrations exceed the limits of the air-purifying respirators.
Product Identifier:	BBO-BASE AO



Date of Last Revision:

BBO-BASE AO

General Hygiene Considerations: Handle according to established industrial hygiene and safety practices. Consult a competent industrial hygienist to determine hazard potential and/or the PPE manufacturers to ensure adequate protection.

SECTION 9. PH	YSICAL AND CHEMICAL PROPERTIES				
Appearance:	Light tan coloured liquid.				
Colour:	Light tan.				
Odour:	Petroleum.				
Odour Threshold:	Not available.				
Physical State:	Liquid.				
pH:	Not available.				
Melting Point / Freezing Point:	-24 °C (-11.2 °F)				
Initial Boiling Point:	> 200 °C (392 °F)				
Boiling Range:	Not available.				
Flash Point:	> 93 °C (199.4 °F) (PMCC)				
Evaporation Rate:	Not available.				
Flammability (solid, gas):	Not applicable.				
Lower Flammability Limit:	Not available.				
Upper Flammability Limit:	Not available.				
Vapor Pressure:	Not available.				
Vapor Density:	Not available.				
Relative Density:	0.8887 (Water = 1)				
Solubilities:	Insoluble in water.				
Partition Coefficient: n- Octanol/Water:	Not available.				
Auto-ignition Temperature	: Not available.				
Decomposition Temperature:	Not available.				
Product Identifier: Date of Preparation:	BBO-BASE AO November 20, 2018				

March 5, 2020



Viscosity:	Not available.
Percent Volatile, wt. %:	Not available.
VOC content, wt. %:	Not available.
Density:	Not available.
Coefficient of Water/Oil Distribution:	Not available.

SECTION 10. STABILITY AND REACTIVITY

Reactivity:	Contact with incompatible materials. Sources of ignition. Exposure to heat.	
Chemical Stability:	Stable under normal storage conditions.	
Possibility of Hazardous Reactions:	None known.	
Conditions to Avoid:	Contact with incompatible materials. Sources of ignition. Exposure to heat.	
Incompatible Materials:	Strong acids. Strong oxidizers. Halogens.	
Hazardous Decomposition Products: Not available.		

SECTION 11. TOXICOLOGICAL INFORMATION

EFFECTS OF Product Toxic	ACUTE EXPOSURE				
Oral:	Not available.				
Dermal:	Not available.				
Inhalation: Component T Component	Not available. oxicity CAS No.	LD50 oral	LD50 dermal	LC ₅₀	
Product Identifier Date of Preparati Date of Last Revi	: on:	BBO-BASE AO November 20, 2018 March 5, 2020			



Gas oils (petroleum), straight-run, high- boiling	68915-97-9	Not available.	Not available.	Not available.
Polycyclic Aromatic Hydrocarbons	130498-29-2	Not available.	Not available.	Not available.
Xylene	1330-20-7	4300 mg/kg (rat)	> 1700 mg/kg (rabbit)	5000 ppm (rat); 4H

Likely Routes of Exposure: Eye contact. Skin contact. Inhalation. Ingestion.

Target Organs:Skin. Eyes. Gastrointestinal tract. Respiratory system.Lungs. Blood. Cardiovascular system. Bone marrow.Liver. Central nervous system.

Symptoms (including delayed and immediate effects)

- Inhalation: May cause respiratory irritation. Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain. This product may contain small amounts of Hydrogen sulphide which may accumulate in confined spaces. Inhalation of Hydrogen sulphide may cause loss of sense of smell, major irritation of the respiratory tract, headache, nausea, vomiting, dizziness, and fluid buildup in the lungs (pulmonary edema), which can be fatal. At 300 ppm unconsciousness may occur after 20 minutes. From 300 to 500 ppm, death can occur within 1 to 4 hours of continuous exposure. At 500 ppm the respiratory system is paralyzed, the victim collapses almost instantaneously, and death can occur after exposure of only 30 to 60 minutes. Above 500 ppm Hydrogen sulphide may cause immediate loss of consciousness; death is rapid, and possibly immediate.
- **Eye:** Causes eye irritation. Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.
- **Skin:** Causes skin irritation. Signs/symptoms may include localized redness, swelling, and itching.
- Ingestion: May be fatal if swallowed and enters airways. May cause gastrointestinal irritation. Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

Skin Sensitization: Not available.

Respiratory Sensitization: Not available.

Medical ConditionsNot available.Aggravated By Exposure:

Product Identifier:	
Date of Preparation:	
Date of Last Revision:	



EFFECTS OF CHRONIC EXPOSURE (from short and long-term exposure)

Target Organs:	Skin. Eyes. Gastrointestinal tract. Respiratory system. Lungs. Blood. Cardiovascular system. Bone marrow. Liver. Central nervous system.

Chronic Effects: Prolonged or repeated contact may dry skin and cause irritation. This product contains Polycyclic Aromatic Hydrocarbons. Prolonged contact with these compounds has been associated with the induction of skin and lung tumours, anemia, disorders of the liver, bone marrow and lymphoid tissues. Repeated exposure of the eyes to high

> concentrations of Xylenes vapour may cause reversible eye damage. Chronic inhalation exposure to xylene causes midfrequency hearing loss in laboratory animals. Xylene reacts synergistically with n-hexane to enhance hearing loss. Hydrogen sulphide may reduce lung function; cause neurological effects such as headaches, nausea, depression and personality changes; eye and mucous membrane irritation; and damage to cardiovascular system.

Carcinogenicity: May cause cancer.

Component Carcinogenicity

Component

Gas oils (petroleum), straight-run, high-boiling Polycyclic Aromatic Hydrocarbons

Xylene

Mutagenicity: Not available.

Reproductive Effects: Not available.

Developmental Effects

Teratogenicity: Not available.

Embryotoxicity: Not available.

Toxicologically Synergistic Materials: Not available.



SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity:	Not available.
Persistence / Degradability:	Not available.
Bioaccumulation / Accumulation	Not available
Mobility In Environment	Not available
Other Adverse Effects	Not available

SECTION 13. DISPOSAL CONSIDERATION

acgih A2	IARC Group 1	NTP List 1	OSHA OSHA Carcinogen.	Prop 65 Listed.
A2	Not listed.	List 2	OSHA Carcinogen.	Listed.
A4	Group 3	Not listed.	Not listed.	Not listed.

Disposal Instructions:

Disposal should be in accordance with applicable regional, national and local laws and regulations. Local regulations may be more stringent than regional or national requirements.

SECTION 14. TRANSPORT INFORMATION

U.S. Department of Transportation (DOT)

- Proper Shipping Name: Not regulated.
- Class: Not applicable.
- UN Number: Not applicable.
- Packing Group: Not applicable.
- Label Code: Not applicable.

Canada Transportation of Dangerous Goods (TDG)

Product Identifier:	BBO-BASE AO
Date of Preparation:	November 20, 2018
Date of Last Revision:	March 5, 2020



Proper Shipping Name:	Not regulated.
Class:	Not applicable.
UN Number:	Not applicable.
Packing Group:	Not applicable.
Label Code:	Not applicable.

SECTION 15. REGULATORY INFORMATION

Chemical Inventories

US (TSCA)

The components of this product are in compliance with the chemical notification requirements of TSCA.

Canada (DSL)

The components of this product are in compliance with the chemical notification requirements of the NSN Regulations under CEPA, 1999.

Federal Regulations

United States

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29

CFR 1910.1200.

SARA Title III

Component	Section Section CERCLA Section RCRA				CAA	
	302 (EHS)	304 EHS	RQ (lbs.)	313	CODE	112(r) TQ
	TPQ (lbs.)	RQ (lbs.)				(lbs.)
Polycyclic Aromatic listed. Hydrocarbons	Not listed.	Not listed.	Not listed. 313	3	Not listed.	Not
Xylene	Not listed.	Not listed.	100	313	U239	Not listed.
State Regulations						

Massachusetts

US Massachusetts Commonwealth's Right-to-Know Law (Appendix A to 105 Code of

Product Identifier:	BBO-BASE AO
Date of Preparation:	November 20, 2018
Date of Last Revision:	March 5, 2020



Massachusetts Regulations Section 670.000)		
Component	CAS No.	RTK List
Gas oils (petroleum), straight-run, high-boiling	68915-97-9	Listed.
Polycyclic Aromatic Hydrocarbons	130498-29-2	Listed.
Xylene	1330-20-7	Listed.
New Jersey		
US New Jersey Worker and Community Right-to	o-Know Act (New Jersey Sta	atute Annotated
Section 34:5A-5)		
Component	CAS No.	RTK List
Gas oils (petroleum), straight-run, high-boiling	68915-97-9	SHHS
Xylene	1330-20-7	SHHS
Note: SHHS = Special Health Hazard Substance		
Pennsylvania		
US Pennsylvania Worker and Community Right	-to-Know Law (34 Pa. Code	Chap. 301-323)
Component	CAS No.	RTK List
Gas oils (petroleum), straight-run, high-boiling	68915-97-9	S
Polycyclic Aromatic Hydrocarbons	130498-29-2	Listed.
Xylene	1330-20-7	E
Note: E = Environmental Hazard; S = Special Hazar	rdous Substance	
California		
California Prop 65: WARNING: This product co	ntains chemicals known to	the State of
California to cause cancer	, birth defects or other repro	ductive harm.
Component	Type of Toxicity	
	Type of Texicity	
Gas oils (petroleum), straight-run, high-boiling	cancer	



SECTION 16. OTHER INFORMATION

4.0

Disclaimer:

The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for their own particular use.

Date of Preparation of SDS: March 5, 2020

Version:

GHS SDS Prepared by: HSE Department

Phone: (403) 618-5213